

PS0224CPSMSC

24V, 2 Amps SMPS with rechargeable Circuit
and dual battery provision lockable MS enclosure

Description



The PS0224CPSMSC is a fully regulated switch mode power supply providing 24 Volts DC at 2 Amps along with the facility of charging the battery for back up. The high frequency action enables it to work smoothly on a very wide AC input Voltage range from 120 to 280 Volts with comparatively low power losses, high efficiency, small size and lesser weight.

FEATURES

Over load cut off & Recovery.
Input Over & Under Voltage protection.
Thermal Shut down Protection and Recovery.
Short circuit and over voltage shutdown protection.
Locable metal and dual battery enclosure

TECHNICAL SPECIFICATIONS

Input Voltage	120-280V AC
Input Frequency	45~55Hz
Output Voltage	24V DC
Output Current	2 Amps. Max
Charging Current	500 mA
Output Voltage adjustment	+ -10%
Efficiency @ full load & 230 V AC	>85%
Operating Temperature	0~55 °C
Line Regulation	<1%
Load Regulation	<1%
Ripple	<50mv p-p
Isolation Between Input & Output	3000V AC
Input & Earth	1500V AC
Output & Earth	1500V AC
Dimensions: L*W*H	310*305*75 (size are in mm)
Weight	1.15 Kg